

Data sheet for three-phase Squirrel-Cage-Motors Innomatics



Motor type : 1CV2082C

INNOMOTICS SD - 80 M - IM B35 - 6p

| | | |
|------------------|-----------------|-----------|
| Client order no. | Item-No. | Offer no. |
| Order no. | Consignment no. | Project |

Remarks

Electrical data **Safe Area**

| U [V] | Δ/Y | f [Hz] | P [kW] | P [hp] | I [A] | n [1/min] | M [Nm] | $\eta^{(3)}$ | | | $\cos\phi^{(3)}$ | | | I_A/I_N | M_A/M_N | M_R/M_N | IE-CL |
|---|------------|--------|---------|--------|-------|-----------|--------|--------------|--|--------------|------------------|------|------------------------|-----------|-----------|-----------|-------|
| | | | | | | | | 4/4 | 3/4 | 2/4 | 4/4 | 3/4 | 2/4 | I_V/I_N | T_A/T_N | T_B/T_N | |
| DOL duty (S1) - 155(F) to 130(B) | | | | | | | | | | | | | | | | | |
| 230 | Δ | 50 | 0.37 | -/- | 1.99 | 925 | 3.8 | 67.6 | 67.9 | 64.4 | 0.69 | 0.60 | 0.47 | 4.0 | 2.1 | 2.4 | IE2 |
| 400 | Y | 50 | 0.37 | -/- | 1.14 | 925 | 3.8 | 67.6 | 67.9 | 64.4 | 0.69 | 0.60 | 0.47 | 4.0 | 2.1 | 2.4 | IE2 |
| 460 | Y | 60 | 0.43 | -/- | 1.22 | 1125 | 3.6 | 64.0 | 64.1 | 61.3 | 0.69 | 0.60 | 0.48 | 4.2 | 2.1 | 2.6 | IE2 |
| 460 | Y | 60 | 0.37 | -/- | 1.15 | 1140 | 3.1 | 64.0 | 63.0 | 59.1 | 0.63 | 0.54 | 0.42 | 4.6 | 2.3 | 2.9 | IE2 |
| IM B35 / IM 2001 | | | FS 80 M | | | IP55 | | UKCA | | IEC/EN 60034 | | | IEC, DIN, ISO, VDE, EN | | | | |
| Environmental conditions : -20 °C - +40 °C / 1000 m | | | | | | | | | Locked rotor time (hot / cold) : 18.90 s 31.60 s | | | | | | | | |

Mechanical data

| | | | | |
|---|---|---|------------------------------------|---|
| Sound level (SPL / SWL) at 50Hz 60Hz | 42.0 / 53.0 dB(A) <small>2) 3)</small> | 45.0 / 56.0 dB(A) <small>2) 3)</small> | Vibration severity grade | A |
| Moment of inertia | 0.0017 kg m ² | | Thermal class | F |
| Bearing DE NDE | 6204 2Z C3 | 6204 2Z C3 | Duty type | S1 |
| Bearing lifetime | | | Direction of rotation | bidirectional |
| L_{10mh} $F_{Rad min}$ for coupling operation 50 60Hz ¹⁾ | 40000 h | 32000 h | Frame material | cast iron |
| Regreasing device | Without | | Net weight of the motor (IM B3) | 16 kg |
| Grease nipple | -/- | | Coating (paint finish) | Standard paint finish C2 |
| Type of bearing | Preloaded bearing DE | | Color, paint shade | RAL7030 |
| Condensate drainage holes | Without | | Motor protection | (B) 1 PTC thermistor - for tripping (2 terminals) |
| External earthing terminal | Without | | Method of cooling | IC411 - self ventilated, surface cooled |
| | | | Carbon footprint (without options) | 41kg |

Terminal box

| | | | |
|---------------------------|---------------------|-----------------------|-----------|
| Terminal box position | top | Main cable entry | 1xM25x1.5 |
| Material of terminal box | cast iron | Main cable gland | 1 plug |
| Type of terminal box | TB1 D01 | Auxiliary cable entry | 1xM16x1.5 |
| Contact screw thread | 6xM4 | Auxiliary cable gland | 1 plug |
| Max. cross-sectional area | 2.5 mm ² | | |

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_R/M_N = break down torque / nominal torque
¹⁾ L_{10mh} according to DIN ISO 281 10/2010
²⁾ at rated power / at full load
³⁾ Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

| | | | | | | |
|---------------------------------|---|--------------------------------------|----------------|---|--------------------------------|-------------|
| Responsible department IN LV | Technical reference | Created by IPC | Approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. | Link documents | |
| INNOMOTICS | Document type Technical data sheet | Document status Released | | | | |
| | Document title 1LE1501-ODC22-2JB4 | Document number TDS-260513-124546 | | | | |
| Restricted | Revision AA | Creation date 2026-05-13 | Language en | | | Page 1/1 |
| © Innomatics 2026 | | | | | | |