

# Data sheet for three-phase Squirrel-Cage-Motors Innomotics



**Motor type : 1CV2073B**

**INNOMOTICS SD - 71 M - IM B35 - 4p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

**Electrical data** **Safe Area**

U [V]	$\Delta/Y$	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{(3)}$			$\cos\phi^{(3)}$			$I_A/I_N$	$M_A/M_N$	$M_R/M_N$	IE-CL
								4/4	3/4	2/4	4/4	3/4	2/4	$I_V/I_N$	$T_A/T_N$	$T_B/T_N$	
<b>DOL duty (S1) - 155(F) to 130(B)</b>																	
230	$\Delta$	50	0.37	-/-	1.77	1380	2.5	72.7	73.2	69.9	0.72	0.63	0.49	4.0	2.5	2.5	IE2
400	Y	50	0.37	-/-	1.02	1380	2.5	72.7	73.2	69.9	0.72	0.63	0.49	4.0	2.5	2.5	IE2
460	Y	60	0.43	-/-	1.04	1680	2.5	72.0	72.4	69.4	0.72	0.63	0.50	4.5	2.6	2.7	IE2
460	Y	60	0.37	-/-	0.96	1705	2.0	72.0	71.2	66.9	0.67	0.58	0.45	5.0	3.0	3.2	IE2
IM B35 / IM 2001			FS 71 M			IP55		UKCA		IEC/EN 60034			IEC, DIN, ISO, VDE, EN				
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 38.80 s   49.60 s								

**Mechanical data**

Sound level (SPL / SWL) at 50Hz 60Hz	59.0 / 67.0 dB(A) <small>2) 3)</small>	59.0 / 67.0 dB(A) <small>2) 3)</small>	Vibration severity grade	A
Moment of inertia	0.0009 kg m <sup>2</sup>		Thermal class	F
Bearing DE   NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
<b>Bearing lifetime</b>			Direction of rotation	bidirectional
$L_{10mh}$ $F_{Rad min}$ for coupling operation 50 60Hz <sup>1)</sup>	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	13 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(B) 1 PTC thermistor - for tripping (2 terminals)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled
			Carbon footprint (without options)	36kg

**Terminal box**

Terminal box position	top	Main cable entry	1xM25x1.5
Material of terminal box	cast iron	Main cable gland	1 plug
Type of terminal box	TB1 D01	Auxiliary cable entry	1xM16x1.5
Contact screw thread	6xM4	Auxiliary cable gland	1 plug
Max. cross-sectional area	2.5 mm <sup>2</sup>		

$I_A/I_N$  = locked rotor current / current nominal  
 $M_A/M_N$  = locked rotor torque / torque nominal  
 $M_R/M_N$  = break down torque / nominal torque  
<sup>1)</sup>  $L_{10mh}$  according to DIN ISO 281 10/2010  
<sup>2)</sup> at rated power / at full load  
<sup>3)</sup> Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LV	Technical reference	Created by IPC	Approved by	<b>Technical data are subject to change! There may be discrepancies between calculated and rating plate values.</b>	<a href="#">Link documents</a>
<b>INNOMOTICS</b>	Document type Technical data sheet	Document status Released			
	Document title <b>1LE1501-OCB32-2JB4</b>	Document number TDS-260415-130032			
Restricted © Innomotics 2026	Revision AA	Creation date 2026-04-15	Language en		Page 1/1