


Three-phase Motor Type*	1TZ9503-1EB43-4_A4	4pole			
Area	Safe Area				
Environmental Conditions	-20°C to +40°C, up to 1000 metres above sea level				
Rated Voltage	400/690V 50Hz, 460VD 60Hz				
Output at 50Hz	22. kW				
Output at 60Hz	25.3 kW				
Frame Size	180L cast iron				
Speed at 50Hz	1470 rpm				
Speed at 60Hz	1770 rpm				
Current at 380V 50Hz	43.4A				
Current at 400V 50Hz	41.A				
Current at 415V 50Hz	39.7A				
Current at 460V 60Hz	41.A				
Efficiency Class (at 50Hz)	IE3				
Percentage Load	125%	100%	75%	50%	25%
Efficiency at 50Hz	92.1%	93.0%	93.6%	93.6%	91.2%
Efficiency at 60Hz	92.7%	93.6%	94.1%	94.0%	91.5%
Power factor (cos fi) at 50Hz	0.85	0.83	0.78	0.68	0.46
Power factor (cos fi) at 60Hz	0.85	0.83	0.78	0.69	0.48
Rated Torque at 50Hz	143. Nm				
Rated Torque at 60Hz	136. Nm				
Duty Cycle	S1				
Starting Current Ratio	6.8 (50Hz)				
Starting Torque Ratio	2.3 (50Hz)				
Breakdown Torque Ratio	3.3 (50Hz)				
Internal Protection / Cooling	IP55 / IC411 (TEFC)				
Insulation Class	F (155°C), temperature rise B (80k)				
Acoustic Pressure	68 dB(A) at 50Hz speed / 70 dB(A) at 60Hz speed				
Standard Mountings	B3, B5, B3/B5				
Weight	170. kg				
Moment of Inertia	0.14 kgm ²				
Bearing DE/NDE	6310 Z C3 / 6310 Z C3 (Bearing located at NDE)				
Bearing Lubrication	Esso Unirex N3				



*The 16th digit of the Type Number denominates the motor mounting.