

Data sheet for three-phase Squirrel-Cage-Motors Innomatics



Motor type : 1CV2073B

INNOMOTICS SD - 71 M - IM B14 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data **Safe Area**

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{(3)}$			$\cos\phi^{(3)}$			I_A/I_N	M_A/M_N	M_R/M_N	M_B/M_N	IE-CL
DOL duty (S1) - 155(F) to 130(B)																		
230	Δ	50	0.37	-/-	1.77	1380	2.5	72.7	73.2	69.9	0.72	0.63	0.49	4.0	2.5	2.5	2.5	IE2
400	Y	50	0.37	-/-	1.02	1380	2.5	72.7	73.2	69.9	0.72	0.63	0.49	4.0	2.5	2.5	2.5	IE2
460	Y	60	0.43	-/-	1.04	1680	2.5	72.0	72.4	69.4	0.72	0.63	0.50	4.5	2.6	2.7	2.7	IE2
460	Y	60	0.37	-/-	0.96	1705	2.0	72.0	71.2	66.9	0.67	0.58	0.45	5.0	3.0	3.2	3.2	IE2

IM B14 / IM 3601	FS 71 M	IP55	UKCA	IEC/EN 60034	IEC, DIN, ISO, VDE, EN
Environmental conditions : -20 °C - +40 °C / 1000 m			Locked rotor time (hot / cold) : 38.80 s 49.60 s		

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	59.0 / 67.0 dB(A) <small>2) 3)</small>	59.0 / 67.0 dB(A) <small>2) 3)</small>	Vibration severity grade	A
Moment of inertia	0.0009 kg m ²		Thermal class	F
Bearing DE NDE	6202 2Z C3	6202 2Z C3	Duty type	S1
Bearing lifetime			Direction of rotation	bidirectional
L_{10mh} $F_{rad min}$ for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Regreasing device	Without		Net weight of the motor (IM B3)	13 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Preloaded bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(B) 1 PTC thermistor - for tripping (2 terminals)
External earthing terminal	Without		Method of cooling	IC411 - self ventilated, surface cooled
			Carbon footprint (without options)	36kg

Terminal box

Terminal box position	top	Main cable entry	1xM25x1.5
Material of terminal box	cast iron	Main cable gland	1 plug
Type of terminal box	TB1 D01	Auxiliary cable entry	1xM16x1.5
Contact screw thread	6xM4	Auxiliary cable gland	1 plug
Max. cross-sectional area	2.5 mm ²		

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_R/M_N = break down torque / nominal torque
¹⁾ L_{10mh} according to DIN ISO 281 10/2010
²⁾ at rated power / at full load
³⁾ Value is valid only for DOL operation with motor design IC411

Transmittal, reproduction, dissemination and/or editing of this document as well as utilization of its contents and communication thereof to others without express authorization are prohibited. Offenders will be held liable for payment of damages. All rights created by patent grant or registration of a utility model or design patent are reserved.

Responsible department IN LV	Technical reference	Created by IPC	Approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
INNOMOTICS	Document type Technical data sheet	Document status Released			
	Document title 1LE1501-OCB32-2KB4	Document number TDS-260415-122147			
Restricted © Innomatics 2026	Revision AA	Creation date 2026-04-15	Language en		Page 1/1