


Three-phase Motor Type*	1TZ9003-1CC03-4_A4	6pole			
Area	Safe Area				
Environmental Conditions	-20°C to +40°C, up to 1000 metres above sea level				
Rated Voltage	400/690V 50Hz, 460VD 60Hz				
Output at 50Hz	3. kW				
Output at 60Hz	3.45 kW				
Frame Size	132S Aluminium frame, cast iron endshields/flanges				
Speed at 50Hz	975 rpm				
Speed at 60Hz	1175 rpm				
Current at 380V 50Hz	6.8A				
Current at 400V 50Hz	6.9A				
Current at 415V 50Hz	6.3A				
Current at 460V 60Hz	6.5A				
Efficiency Class (at 50Hz)	IE3				
Percentage Load	125%	100%	75%	50%	25%
Efficiency at 50Hz	84.5%	85.6%	86.1%	84.9%	79.3%
Efficiency at 60Hz	88.3%	89.5%	89.9%	89.0%	84.1%
Power factor (cos fi) at 50Hz	0.77	0.73	0.65	0.52	0.32
Power factor (cos fi) at 60Hz	0.78	0.74	0.67	0.54	0.34
Rated Torque at 50Hz	30. Nm				
Rated Torque at 60Hz	28. Nm				
Duty Cycle	S1				
Starting Current Ratio	6.6 (50Hz)				
Starting Torque Ratio	2.3 (50Hz)				
Breakdown Torque Ratio	3.2 (50Hz)				
Internal Protection / Cooling	IP55 / IC411 (TEFC)				
Insulation Class	F (155°C), temperature rise B (80k)				
Acoustic Pressure	58 dB(A) at 50Hz speed / 62 dB(A) at 60Hz speed				
Standard Mountings	B3, B5, B3/B5, B14A, B3/B14A				
Weight	43. kg				
Moment of Inertia	0.037 kgm ²				
Bearing DE/NDE	6308 2Z C3 / 6308 2Z C3 (Bearing located at NDE)				
Bearing Lubrication	Esso Unirex N3				



*The 16th digit of the Type Number denominates the motor mounting.