


Three-phase Motor Type*	1TZ9003-1DA33-4_A4	2pole			
Area	Safe Area				
Environmental Conditions	-20°C to +40°C, up to 1000 metres above sea level				
Rated Voltage	400/690V 50Hz, 460VD 60Hz				
Output at 50Hz	15. kW				
Output at 60Hz	17.3 kW				
Frame Size	160M Aluminium frame, cast iron endshields/flanges				
Speed at 50Hz	2960 rpm				
Speed at 60Hz	3560 rpm				
Current at 380V 50Hz	28.5A				
Current at 400V 50Hz	27.A				
Current at 415V 50Hz	26.1A				
Current at 460V 60Hz	27.A				
Efficiency Class (at 50Hz)	IE3				
Percentage Load	125%	100%	75%	50%	25%
Efficiency at 50Hz	91.4%	91.9%	91.9%	91.0%	86.4%
Efficiency at 60Hz	91.4%	91.7%	91.5%	90.3%	85.4%
Power factor (cos fi) at 50Hz	0.89	0.87	0.82	0.73	0.50
Power factor (cos fi) at 60Hz	0.90	0.88	0.84	0.75	0.55
Rated Torque at 50Hz	48. Nm				
Rated Torque at 60Hz	46. Nm				
Duty Cycle	S1				
Starting Current Ratio	8.8 (50Hz)				
Starting Torque Ratio	2.8 (50Hz)				
Breakdown Torque Ratio	4.3 (50Hz)				
Internal Protection / Cooling	IP55 / IC411 (TEFC)				
Insulation Class	F (155°C), temperature rise B (80k)				
Acoustic Pressure	70 dB(A) at 50Hz speed / 77 dB(A) at 60Hz speed				
Standard Mountings	B3, B5, B3/B5, B14A, B3/B14A				
Weight	84. kg				
Moment of Inertia	0.061 kgm ²				
Bearing DE/NDE	6309 2Z C3 / 6309 2Z C3 (Bearing located at NDE)				
Bearing Lubrication	Esso Unirex N3				



*The 16th digit of the Type Number denominates the motor mounting.