


Three-phase Motor Type*	1TZ9503-3AD03-4_A4	8pole			
Area	Safe Area				
Environmental Conditions	-20°C to +40°C, up to 1000 metres above sea level				
Rated Voltage	400/690V 50Hz, 460VD 60Hz				
Output at 50Hz	55. kW				
Output at 60Hz	66. kW				
Frame Size	315S Cast iron				
Speed at 50Hz	740 rpm				
Speed at 60Hz	888 rpm				
Current at 380V 50Hz	112.A				
Current at 400V 50Hz	106.A				
Current at 415V 50Hz	102.A				
Current at 460V 60Hz	108.A				
Efficiency Class (at 50Hz)	IE3				
Percentage Load	125%	100%	75%	50%	25%
Efficiency at 50Hz	91.7%	92.5%	92.9%	92.6%	89.6%
Efficiency at 60Hz	92.8%	93.6%	94.0%	93.7%	90.7%
Power factor (cos fi) at 50Hz	0.83	0.81	0.76	0.65	0.43
Power factor (cos fi) at 60Hz	0.84	0.82	0.78	0.68	0.44
Rated Torque at 50Hz	710. Nm				
Rated Torque at 60Hz	710. Nm				
Duty Cycle	S1				
Starting Current Ratio	6.0 (50Hz)				
Starting Torque Ratio	2.3 (50Hz)				
Breakdown Torque Ratio	2.7 (50Hz)				
Internal Protection / Cooling	IP55 / IC411 (TEFC)				
Insulation Class	F (155°C), temperature rise B (80k)				
Acoustic Pressure	66 dB(A) at 50Hz speed / 69 dB(A) at 60Hz speed				
Standard Mountings	B3, B5, B3/B5				
Weight	650. kg				
Moment of Inertia	2. kgm ²				
Bearing DE/NDE	6319 C3 / 6319 C3 (Bearing located at NDE)				
Bearing Lubrication	Esso Unirex N3				



*The 16th digit of the Type Number denominates the motor mounting.